


System analysis, Source-Path-Receptor approach

Project KIIK (water authority HHSK)



The flood protection assignment



- Nearly 60% of The Netherlands is vulnerable to flooding
- Most of Dutch population in that area
- Climate change and land subsidence
- Flood Protection Programme (the execution department of the Delta programme) keeps The Netherlands safe
- Project KIIJK is one the 300 projects

Source (1)



- Tidal river connected to North Sea
- Wind
- Precipitation in the area or upstream with high discharge
- Climate change worsens effects
- Land subsidence 1,1 cm/yr



Source (2)



The Hollandse IJssel

By lowering the maximum water level by closing the Storm Surge Barrier earlier in time when extreme weather is predicted.



Storm Surge Barrier

By optimizing the failure probability of the Barrier.



Floodplains (2,1km)

By using the strength of floodplains in calculating the safety of the dike.



Dike

Next to traditional solutions, innovative techniques (like nails) or advanced calculation tools are possible.




Polder

By minimizing the impact of a flooding (water retention area) or by reinforcing a secondary flood protection.




Pathway (1)



landward macro-
instability




riverward macro-
instability




micro-instability


Failure mechanisms project KIJK



wave overtopping
and wave run-up




revetment instability
(top soil layer)



floodplain instability

Receptor (1)



Receptor (2)



Flood protection assignment

- Total of 10,15 km (red line)




Human environment

- 740 buildings
- 3 villages
- Many monuments
- Heavy traffic



Receptor (3)



This means...

